


# LEVEL 1 LOW SPALL GLAZING

1-1803-LS



## LEVEL 1 LOW SPALL GLAZING

1-1803-LS

### SPECIFICATIONS

#### BALLISTIC RATING: MEETS OR EXCEEDS THE FOLLOWING

- UL752 LEVEL 1 BALLISTIC STANDARD

#### FRAMING OPTIONS

- ALUMINUM STORE FRONT
- ALUMINUM CURTAIN WALL

#### TECHNICAL DATA

THIS BALLISTIC GLAZING WILL WITHSTAND 3 ROUNDS OF 9MM IN A ONE SQUARE FOOT SAMPLE, UTILIZING A FMJ PROJECTILE WITH A MASS OF 124 GRAIN (8 GRAM) TRAVELING AT 1293 FEET / SECOND (394.1 METERS / SECOND) WITH EACH ROUND DELIVERING AN IMPACT OF 625 JOULES OF ENERGY AND A MOMENTUM OF 3.17KG M/S. THIS BALLISTIC GLAZING MAY ALSO PROVIDE UP TO 20 MINUTES OF FORCED ENTRY PROTECTION.

- NOMINAL THICKNESS: 3/4"; 0.7"; 17.78MM
- WEIGHT PER SQUARE FOOT: 6.9 LBS; 3.1326KG

#### SIZING INFORMATION

- UP TO 70" X 128"

#### TESTING CERTIFICATIONS

- BGAS0418222



TESTED TO  
**3 ROUNDS  
OF 9MM**

