

LEVEL 1 LOW SPALL GLAZING

1-1901-LS AGL

VARIOUS INTERLAYERS
GLASS, POLYCARBONATE &
POLYURETHANE



1.185"

WEIGHT
15.6 LBS

LEVEL 1 LOW SPALL GLAZING

1-1901-LS AGL

SPECIFICATIONS

BALLISTIC RATING: MEETS OR EXCEEDS THE FOLLOWING

- UL752 LEVEL 1 BALLISTIC STANDARD

TECHNICAL DATA

THIS BALLISTIC GLAZING WILL WITHSTAND 3 ROUNDS OF 9MM IN A ONE SQUARE FOOT SAMPLE, UTILIZING A FMJ PROJECTILE WITH A MASS OF 124 GRAIN (8 GRAM) TRAVELING AT 1293 FEET / SECOND (394.1 METERS / SECOND) WITH EACH ROUND DELIVERING AN IMPACT OF 625 JOULES OF ENERGY AND A MOMENTUM OF 3.17KG M/S. THIS BALLISTIC GLAZING MAY ALSO PROVIDE UP TO 20 MINUTES OF FORCED ENTRY PROTECTION.

- NOMINAL THICKNESS: 1 1/8"
- WEIGHT PER SQUARE FOOT: 14.85 LBS

FRAMING OPTIONS

- ALUMINUM STORE FRONT
- ALUMINUM CURTAIN WALL

SIZING INFORMATION

- UP TO 70" X 128"

TESTING CERTIFICATIONS

- N/A



TESTED TO
**3 ROUNDS
OF 9MM**

