

LEVEL 7 NO SPALL GLAZING

7-2003-NS/G7

VARIOUS INTERLAYERS
GLASS, POLYCARBONATE &
POLYURETHANE



1.31"

WEIGHT
12.673 LBS

LEVEL 7 NO SPALL GLAZING

7-2003-NS/G7



TESTED TO
5 ROUNDS
OF 5.56

SPECIFICATIONS

BALLISTIC RATING: MEETS OR EXCEEDS THE FOLLOWING

- UL752 LEVEL 7 BALLISTIC STANDARD

TECHNICAL DATA

THIS BALLISTIC GLAZING WILL WITHSTAND 5 ROUNDS OF .223 (5.56) IN A ONE SQUARE FOOT SAMPLE, UTILIZING A FMJ PROJECTILE WITH A MASS OF 55 GRAIN (3.56 GRAM) TRAVELING AT 3234 FEET / SECOND (986.4 METERS / SECOND) WITH EACH ROUND DELIVERING AN IMPACT OF 731 JOULES OF ENERGY AND A MOMENTUM OF 3.51 KG M/S. THIS BALLISTIC GLAZING MAY ALSO PROVIDE UP TO 30 MINUTES OF FORCED ENTRY PROTECTION.

- NOMINAL THICKNESS: 1 5/16"
- WEIGHT PER SQUARE FOOT: 12.673 LBS; 5.748KG

FRAMING OPTIONS

- ALUMINUM STORE FRONT
- ALUMINUM CURTAIN WALL

SIZING INFORMATION

- UP TO 70" X 128"

TESTING CERTIFICATIONS

- NTS BGA20001-1

