


LEVEL 4 NO SPALL GLAZING 4-1811-NS



LEVEL 4 NO SPALL GLAZING 4-1811-NS



TESTED TO
**1 ROUND
OF 30.06**

SPECIFICATIONS

BALLISTIC RATING: MEETS OR EXCEEDS THE FOLLOWING

- UL752 LEVEL 4 BALLISTIC STANDARD

TECHNICAL DATA

THIS BALLISTIC GLAZING WILL WITHSTAND 1 ROUND OF 30.06 (7.62X63) IN A ONE SQUARE FOOT SAMPLE, UTILIZING A LEAD CORE PROJECTILE WITH A MASS OF 180 GRAIN (11.67 GRAM) TRAVELING AT 2667 FEET / SECOND (813.4 METERS / SECOND) WITH EACH ROUND DELIVERING AN IMPACT OF 3853 JOULES OF ENERGY AND A MOMENTUM OF 9.48 KG M/S. THIS BALLISTIC GLAZING MAY ALSO PROVIDE UP TO 30 MINUTES OF FORCED ENTRY PROTECTION.

- NOMINAL THICKNESS: 1 1/8"
- WEIGHT PER SQUARE FOOT: 13 LBS

FRAMING OPTIONS

- STEEL
- ALUMINUM

SIZING INFORMATION

- UP TO 70" X 128"

TESTING CERTIFICATIONS

- BGA23003-1

